Specifications BuzziSkin

Composition 100% Recycled P.E.T. Felt, selfadhesive backing
Weight 1.000 g/m² | 29.49 oz/yd²
Width 98 cm | 38.58″
Thickness 6,1 mm | 0.24″
Abrasion resistance >7.000 Martindale
Flammability EU: EN 13501.1:2013 Class C-s2,d0
USA: ASTM E84 Class A certified
Fastness to light USA 5
⚠ **Application & Installation Restrictions** see installation manual

Maintenance BuzziSkin

Vacuum clean regularly. Don't wash. Don't remove the BuzziSkin from the product. Treat spillages immediately. Professional dry clean or wipe clean with a pH neutral soap and a damp cloth.

Specifications BuzziFelt

Composition 100% Recycled P.E.T. Felt, latex backing
Weight 1.000 g/m² | 29.49 oz/yd²
Width 170 cm | 66.93″
Thickness 6 mm | 0.236″
Abrasion resistance >7.000 Martindale
Flammability EU: EN 13501.1 + A1/2009 Class B-s1,d0
USA: ASTM E84 Class A certified
Fastness to light USA 5

Maintenance BuzziFelt

Vacuum clean regularly. Don't wash. Don't remove the BuzziFelt from the product. Treat spillages immediately. Professional dry clean or wipe clean with a pH neutral soap and a damp cloth.

BuzziSkin | BuzziFelt


NO BOUNDARIES


samples@buzzi.space | usa.samples@buzzi.space | **www.buzzi.space**

M0026-SALES.02.1


BuzziSkin


SK-Anthracite 68


SK-Jeans 75



SK-StoneGrey 67


SK-LightBlue 60


SK-EcoBrown 58



SK-Mokka 74


SK-OffWhite 63


SK-Curry 61


SK-Red 59



SK-Orange 66



SK-Pink 65


SK-Lime 64


BuzziFelt


FE-LightBlue 60


FE-StoneGrey 67


FE-Jeans 75


FE-Anthracite 68


FE-Curry 61


FE-OffWhite 63


FE-Mokka 74


FE-EcoBrown 58



FE-Lime 64


FE-Pink 65


FE-Orange 66


FE-Red 59

Front


SK-Jeans 75

Back



Back



Front


FE-Mokka 74

Batch to batch variations in shade & density may occur | Application overview & latest update **www.buzzi.space**