TRIAFLEX
SITZ- UND ARBEITSPLATZSYSTEME

CONNECT SPECIFICATIONS

Design no.		2515/2516/2517/2518
Application		contract
Composition		48% Wool, 41% post-consumer rec pes, 9% pa, 2% pes
Weight	g/lm oz/lin.yd	370 11.93
Width	cm inches	140 55
Abrasion	rubs martindale (EN ISO 12947-2) rubs martindale (ASTM D4966-02) (heavy duty upholstery)	90,000 60,000
Pilling	scale 1-5, max. 5 - EN ISO 12945-2	4-5
Light fastness	scale 1-8, max. 8 - EN ISO 105-B02	5-7
Rubbing fastness	scale 1-5, max. 5 - EN ISO 105x12 (wet/dry)	4-5/4-5
Maintenance	dry cleaning P(S)  dry cleaning	
US ACT	CA TB 117-2013 AATCC 8 or 116 Wet/dry crocking AATCC 16 Light fastness ASTM D4970 Pilling ASTM D4966 Martindale (heavy duty)	pass pass pass pass pass
Flammability	BS EN 1021-1 Cigarette BS EN 1021 1&2 Cigarette and Match BS 5852 Crib 5 CA TB 117-2013 Class Uno UNI 9175 Class 1 I EMME Will also pass other flammability standards. Flame retardant performance is dependent upon the foam used. Contains no flame retardant chemicals.	
Certificates		**Complete list**
Environment	STANDARD 100 by OEKO-TEX® EU Ecolabel	
Design	Cenk Kivrikoglu	
Colours	Cenk Kivrikoglu	